

Parts Export

Generated: 2026-03-30 00:29:06

Total Parts: 5

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EDA-00002-A	10-Pin Alligator Clip to Female Dupont Jumper Wire (20cm)	MM - Mechanical Module	Generic / OEM, KEYESTUDIO, SunFounder, DFRobot	10-pin jumper wire set featuring insulated alligator (crocodile) clips on one end and female Dupont connectors on the other. Designed for quick and secure temporary electrical connections in DIY projects, prototyping, and laboratory testing. Widely used in school physics labs, breadboard testing, circuit assembly, and component holding during soldering.	Item Type: Electronics Accessory Jumper Type: Female Clip Length: 22.6 mm Cable Length: 20 cm Material: Copper with Plastic Insulation Shipping Weight: 0.04 kg Shipping Dimensions: 7 x 4 x 2 cm	Alligator Clip Wire • Dupont Jumper Wire • 10 Pin Jumper • Crocodile Clip Cable • 20cm Test Lead
	EMA-00006-B	Passive Buzzer Module	EM - Electronic-Electrical Modules	ED Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Passive buzzer module designed to generate variable tones using PWM or frequency control. Operates from 1.5V to 15V DC and produces tones in the 1.5–2.5 kHz range. Ideal for alarms, alerts, Arduino projects, and microcontroller-based sound applications.	Model: Passive Buzzer Module Operating Voltage (VDC): 1.5 – 15 Max Operating Current (mA): 25 Tone Generator Frequency Range (kHz): 1.5 – 2.5 Mounting Type: PCB Mount Pin Pitch: 2.54 mm Compatibility: Arduino / Microcontrollers Length (mm): 15 Width (mm): 19.7 Height (mm): 10 Weight (g): 1 (approx.) Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H): 6 x 4 x 2 cm	Passive Buzzer • KY-006 Module • Arduino Buzzer • PWM Buzzer • Sound Module
	EMS-00002-A	DHT11 Temperature and Humidity Sensor Module with LED	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Digital temperature and humidity sensor module with calibrated single-wire serial output. Features onboard pull-up resistor and LED status indicator for easy interfacing. Ideal for weather stations, environmental monitoring, and smart automation projects.	Item Type: Sensor Model: DHT11 Temperature and Humidity Sensor Measuring Temperature Range (°C): 0 – 50 Temperature Accuracy: ± 2 °C Humidity Range: 20 – 95 % RH Humidity Accuracy: ± 5 % RH Resolution: 16 bit Output Form: Digital Output (Single Wire Serial) Operating Voltage (VDC): 3 – 5 Operating Current (mA): ? 2.5 Dimensions (L x W x H mm): 31 x 14 x 7.5 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H cm): 5 x 5 x 2	DHT11 • Temperature Sensor • Humidity Sensor • Digital Temp Sensor • Arduino Climate Sensor
	EMS-00017-B	Light Dependent Resistor (LDR) Module	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	The LDR Module detects ambient light intensity and provides a digital output based on brightness level. It features an onboard potentiometer to adjust sensitivity and threshold detection. Ideal for automatic lighting systems, Arduino projects, and light-based automation applications.	Model: Light Dependent Resistor Module Operating Voltage (V): 3.3 – 5 Operating Current (mA): 15 Output Type: Digital (DO) Adjustable Threshold: Yes (via Potentiometer) Sensor Type: Photoresistor (LDR) Mounting Hole: M3 Indicator LEDs: Power LED, Status LED Pin Configuration: VCC, GND, DO Length (mm): 36 Width (mm): 14 Height (mm): 8 Weight (g): 3 Shipping Weight: 0.005 kg Shipping Dimensions (L x W x H): 4 x 3 x 2 cm	LDR Module • Light Sensor • Photoresistor Module • LM393 Sensor • Arduino Light Sensor
	EMS-00020-A	PS2 Joystick Module Breakout Sensor	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Dual-axis analog joystick module used to detect X and Y movement positions. Each axis uses a 10KΩ potentiometer providing 0–5V analog output. Includes built-in push-button switch, ideal for robotics, gaming, and motion control projects.	Model: PS2 Joystick Module Operating Voltage (VDC): 5 Potentiometer Resistance: 10K? (per axis) X/Y Output: Analog (0–5V) Button: Digital (Press-Down) Interface Type: 2.54 mm Pin Header PCB Size (mm): 34 x 32 Compatibility: Arduino / Raspberry Pi / Microcontrollers Lifespan: Long-Life, High-Stability Potentiometers Shipping Weight: 0.015 kg Shipping Dimensions (L x W x H): 6 x 5 x 4 cm	PS2 Joystick • Analog Joystick Module • Dual Axis Sensor • 10K Potentiometer Joystick • Arduino Joystick