

Parts Export

Generated: 2026-03-30 02:08:58

Total Parts: 6

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	COC-00004-A	Desoldering Wick 1.5m (100% Copper)	CO - Consumables	Generic	Finely braided 100% copper wick for fast and clean solder removal from electronic joints. Works with a heated soldering iron; flux-assisted for efficient molten solder absorption. Essential for PCB repair, rework, and general electronics maintenance tasks.	Item Type: Desoldering Wick Material: Suitable for Comfortable Desoldering Length: 1.5 m Width: 1.85 mm Thickness: Suitable for Comfortable Desoldering Application: Faster & Cleaner Electronics Desoldering Shipping Weight: 0.008 kg Shipping Dimensions (L × W × H): 6 × 5 × 1 cm	Desoldering Wick • Solder Braid • PCB Repair • 100% Copper • Solder Removal • Flux-Assisted • Electronics Rework • 1.5m
	COC-00007-A	Soldering Flux Paste (10g)	CO - Consumables	Generic / OEM, Noel, Welfix, Mechanic, Pro'sKit	This soldering flux paste is designed to improve solder flow and enhance joint quality during soldering and desoldering operations. It contains high-quality additives and activators for effective bonding. The paste is prepared using standardized formulations to ensure consistent performance. It reduces oxidation and ensures clean and reliable solder joints. Suitable for general-purpose soldering of electrical wires, PCB components, and cables. Ideal for DIY users, students, and professional technicians.	Item Type: Soldering Flux Paste Net Weight: 10 g Color: White / Yellow (as per brand batch) Usage: PCB, Wires, Electrical Components Packaging Type: Small Plastic Container	Flux Paste • 10g • Soldering Flux • PCB Repair • Low Smoke
	EDA-00002-A	10-Pin Alligator Clip to Female Dupont Jumper Wire (20cm)	MM - Mechanical Module	Generic / OEM, KEYESTUDIO, SunFounder, DFRobot	10-pin jumper wire set featuring insulated alligator (crocodile) clips on one end and female Dupont connectors on the other. Designed for quick and secure temporary electrical connections in DIY projects, prototyping, and laboratory testing. Widely used in school physics labs, breadboard testing, circuit assembly, and component holding during soldering.	Item Type: Electronics Accessory Jumper Type: Female Clip Length: 22.6 mm Cable Length: 20 cm Material: Copper with Plastic Insulation Shipping Weight: 0.04 kg Shipping Dimensions: 7 × 4 × 2 cm	Alligator Clip Wire • Dupont Jumper Wire • 10 Pin Jumper • Crocodile Clip Cable • 20cm Test Lead
	EDD-00002-A	Red LED (10mm, DIP Type)	ED - Electronic Device	Generic	Red Light Emitting Diode (LED) used as an indicator in electronic circuits. Emits bright red light when powered, ideal for TVs, monitors, telephones, computers. Suitable for general indicator applications, prototyping, and electronics projects.	Case/Package: DIP Diameter (mm): 10 Mounting Type: Through Hole Lens Appearance: Transparent Color: Red Forward Voltage (V): 2 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Dimensions (L × W × H): 1 × 1 × 1 cm	Red LED • Indicator LED • Through Hole LED • DIP LED • 10mm LED
	EDD-00002-C	Yellow LED (10mm, DIP Type)	ED - Electronic Device	Generic	Yellow Light Emitting Diode (LED) used as an indicator in electronic circuits. Emits bright yellow light with a transparent body, ideal for TVs, monitors, telephones, and computers. Suitable for general indicator applications, prototyping, and project indicator panels.	Case/Package: DIP Diameter (mm): 10 Mounting Type: Through Hole Lens Appearance: Transparent Color: Yellow Forward Voltage (V): 3.2 Forward Current (mA): 30 Shipping Weight: 0.001 kg Shipping Dimensions (L × W × H): 1 × 1 × 1 cm	Indicator LED • Through Hole LED • DIP LED • 10mm LED • Yellow LED
	EDR-00002-10K0	10K? Potentiometer (3-Pin, 15mm Shaft)	ED - Electronic Device	ED Series / Generic Compatible, Bourns, Alpha, Omega	10KΩ rotary potentiometer used for adjusting voltage, current, and signal levels in electronic circuits. Features smooth single-turn rotation with a durable 15mm shaft and through-hole mounting. Ideal for audio control, Arduino analog input, sensor calibration, and embedded system tuning.	Manufacturer: Generic Resistance (Ohm): 10K Tolerance (%): 20 Temperature Coefficient: ±100ppm/°C Operating Temperature (°C): -40 to 80 Mounting Type: Through Hole Shaft Type: 15mm Rotary Shaft Adjustment Type: Single Turn Length (mm): 20 Width (mm): 17 (Body Diameter) Height (mm): 24 Weight (g): 6 Shipping Weight: 0.001 kg Shipping Dimensions (L × W × H): 1 × 1 × 1 cm	10K Potentiometer • Rotary Pot • Variable Resistor • WH148 Potentiometer • 3-Pin Pot