

# Parts Export

Generated: 2026-03-30 06:20:42

Total Parts: 3

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	<b>EDK-00004-A</b>	Metal Film Resistor Assorted Kit (600 pcs, 30 Values)	ED - Electronic Device	Generic	Assorted kit of 600 metal film resistors with 30 different values, 20 pcs each. 1/4W, 1% tolerance resistors suitable for precise electronic, DIY, and educational projects.	Manufacturer: Generic Model Name: 600 pcs. Metal Film Resistor Assorted kit – 30 Kinds Power Rating: 1/4W Tolerance (%): 1 Material Type: Metal Film Package Type: Axial Lead Temperature Stability: High (Better than Carbon Film) Noise Level: Low Frequency Suitability: Suitable for RF and High-Frequency Applications Number of Values: 30 Total Quantity: 600 pcs Quantity per Value: 20 pcs Shipping Weight: 0.001 kg Shipping Dimensions (L x W x H): 1 x 1 x 1 cm	Ideal for prototyping • learning resistor color codes • testing • and circuit experiments.
	<b>EMA-00006-B</b>	Passive Buzzer Module	EM - Electronic-Electrical Modules	ED Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Passive buzzer module designed to generate variable tones using PWM or frequency control. Operates from 1.5V to 15V DC and produces tones in the 1.5&ndash;2.5 kHz range. Ideal for alarms, alerts, Arduino projects, and microcontroller-based sound applications.	Model: Passive Buzzer Module Operating Voltage (VDC): 1.5 – 15 Max Operating Current (mA): 25 Tone Generator Frequency Range (kHz): 1.5 – 2.5 Mounting Type: PCB Mount Pin Pitch: 2.54 mm Compatibility: Arduino / Microcontrollers Length (mm): 15 Width (mm): 19.7 Height (mm): 10 Weight (g): 1 (approx.) Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H): 6 x 4 x 2 cm	Passive Buzzer • KY-006 Module • Arduino Buzzer • PWM Buzzer • Sound Module
	<b>EMC-00004-A</b>	HC-05 6-Pin Wireless Serial Bluetooth Module with Button	EM - Electronic-Electrical Modules	HC Series / Generic Compatible, Waveshare, KEYESTUDIO, SunFounder	The HC-05 Bluetooth Module is a 6-pin wireless serial communication device designed for UART-based data transfer between microcontrollers and Bluetooth-enabled devices. Operates in the 2.4GHz ISM band using GFSK modulation and supports both Master and Slave modes. Supports AT command configuration and includes an onboard push button for AT mode entry.	Operating Voltage: 3.6V – 6V DC Input Current: 50 mA Operating Frequency: 2.4 GHz ISM Band Modulation Type: GFSK (Gaussian Frequency Shift Keying) Emission Power: 4 dBm (Class 2) Receiver Sensitivity: -84 dBm at 0.1% BER Maximum Range: 10 meters (typical) Interface Pins: EN/KEY, VCC, GND, TXD, RXD, STATE AT Command Support: Yes Onboard Button: Yes (AT Mode Selection) Length (mm): 43 Width (mm): 16.5 Height (mm): 7 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (cm): 5 x 3 x 1	HC-05 • Bluetooth Module • UART Bluetooth • 6-Pin Bluetooth • Master Slave Module • Arduino Bluetooth