

Parts Export

Generated: 2026-03-30 01:03:53

Total Parts: 6

Image	Part Number	Name	Category	Manufacturer	Description	Specification	Tags
	EMS-00001-A	MQ-2 Smoke LPG Butane Hydrogen Gas Sensor Detector Module	EM - Electronic-Electrical Modules	Hanwei Electronics Group Corporation, Zhengzhou Winsen Electronics Technology Co., Ltd.	The MQ-2 Gas Sensor Module detects combustible gases such as LPG, methane, hydrogen, alcohol vapor, and smoke. It uses a SnO ₂ sensing element and provides both analog and digital outputs with adjustable sensitivity. Ideal for gas leakage detection, safety systems, and Arduino-based environmental monitoring projects.	Sensor Model: MQ-2 Detection Range: 300 – 10,000 ppm Detectable Gases: LPG, Butane, Propane, Methane (CH ₄), Hydrogen (H ₂), Alcohol, Smoke, CO Sensing Material: Tin Dioxide (SnO ₂) Operating Voltage: 5V DC Digital Output Voltage: 0V or 5V (TTL Logic) Analog Output: Yes Sensitivity Adjustment: Onboard Potentiometer Preheat Time: 20 seconds (minimum) Dimensions (mm): 36 x 20 x 21 Weight (g): 8 Shipping Weight: 0.012 kg Shipping Dimensions (cm): 4 x 4 x 4	Arduino Compatible • MQ-2 Sensor • LPG Gas Sensor • Smoke Detector • SnO ₂ Sensor • Combustible Gas Module • 5V Gas Sensor • Gas Leakage Detector
	EMS-00002-A	DHT11 Temperature and Humidity Sensor Module with LED	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Digital temperature and humidity sensor module with calibrated single-wire serial output. Features onboard pull-up resistor and LED status indicator for easy interfacing. Ideal for weather stations, environmental monitoring, and smart automation projects.	Item Type: Sensor Model: DHT11 Temperature and Humidity Sensor Measuring Temperature Range (°C): 0 – 50 Temperature Accuracy: ± 2 °C Humidity Range: 20 – 95 % RH Humidity Accuracy: ± 5 % RH Resolution: 16 bit Output Form: Digital Output (Single Wire Serial) Operating Voltage (VDC): 3 – 5 Operating Current (mA): ? 2.5 Dimensions (L x W x H mm): 31 x 14 x 7.5 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (L x W x H cm): 5 x 5 x 2	DHT11 • Temperature Sensor • Humidity Sensor • Digital Temp Sensor • Arduino Climate Sensor
	EMS-00005-A	Ultrasonic Distance Sensor (HC-SR04+)	EM - Electronic-Electrical Modules	MWduino / Generic, ElecFreaks, KEYESTUDIO, SunFounder	Ultrasonic distance sensor module using 40kHz sound waves for accurate measurement. Operates on 3.3V and 5V DC with 4-pin interface (VCC, Trig, Echo, GND). Ideal for robotics, obstacle detection, automation, and distance sensing projects.	Power Supply (V): +5V DC Working Current (mA): 15 mA Output Signal: Electrical frequency signal Ranging Distance: 2 cm – 400 cm Distance Resolution: 0.3 cm Measuring Angle: 30° Operating Voltage Range (V): 3.3V – 5.5V Interface Type: 4-pin (VCC, Trig, Echo, GND) Shipping Weight: 0.007 kg Shipping Dimensions (L x W x H): 9 x 6 x 2 cm	Ultrasonic Sensor • HC-SR04+ • Distance Sensor • Arduino Sensor • Obstacle Detection Module
	EMS-00013-A	Infrared Obstacle Avoidance IR Sensor Module	EM - Electronic-Electrical Modules	Generic OEM Manufacturer, Keyestudio, HiLetgo, Elegoo, SunFounder	The Infrared Obstacle Avoidance Sensor Module detects nearby objects using reflected infrared light. It uses an IR transmitter and receiver pair with an LM393 comparator to provide a digital active LOW output when an obstacle is detected. Ideal for robotics, smart cars, automation systems, and Arduino-based proximity detection projects.	Sensor Type: Infrared Reflective Obstacle Sensor Operating Voltage: 3.6V - 5V DC Output Type: Digital (Active Low) Main IC: LM393 Comparator Average Current Consumption: 0.06 mA Detection Angle: 35° Detection Distance: 2 cm – 30 cm (adjustable) Interface Pins: VCC, GND, OUT Indicator LED: Yes (Obstacle Detection Indicator) Sensitivity Adjustment: Onboard Potentiometer Dimensions (mm): 48 x 14 x 8 Weight (g): 5 Shipping Weight: 0.01 kg Shipping Dimensions (cm): 5 x 4 x 1	IR Obstacle Sensor • Infrared Reflective Module • LM393 Comparator • Active Low Output • Proximity Sensor • Arduino Compatible • Robot Sensor
	EMS-00019-A	Soil Moisture sensor	EM - Electronic-Electrical Modules	Sensor Probe Manufacturer, Comparator Module Manufacturer, IC Manufacturer	The Soil Moisture Sensor Module (YL-69 + FC-28) is a resistive soil humidity detection device used to measure water content in soil. It provides both analog (AO) and digital (DO) outputs with adjustable sensitivity using an onboard LM393 comparator. Ideal for smart irrigation systems, plant monitoring, Arduino, and IoT-based environmental projects.	Sensor Type: Resistive Soil Moisture Sensor Operating Voltage: 3.3V – 5V DC Output Type: Analog (AO) and Digital (DO) Digital Output: 0 or 1 (TTL Logic) Measurement Principle: Resistance-based conductivity measurement Sensitivity Adjustment: Onboard Potentiometer (for digital threshold) Probe Dimension: Approx. 6 cm x 3 cm Cable Length: 20 cm Interface Pins: VCC, GND, DO, AO Shipping Weight: 0.02 kg Shipping Dimensions (cm): 8 x 6 x 3	Arduino Compatible • Soil Moisture Sensor • YL-69 • FC-28 • LM393 • Resistive Soil Sensor • Irrigation Sensor
	EMS-00020-A	PS2 Joystick Module Breakout Sensor	EM - Electronic-Electrical Modules	EM Series / Generic Compatible, KEYESTUDIO, SunFounder, DFRobot	Dual-axis analog joystick module used to detect X and Y movement positions. Each axis uses a 10KΩ potentiometer providing 0–5V analog output. Includes built-in push-button switch, ideal for robotics, gaming, and motion control projects.	Model: PS2 Joystick Module Operating Voltage (VDC): 5V Potentiometer Resistance: 10KΩ (per axis) X/Y Output: Analog (0–5V) Button: Digital (Press-Down) Interface Type: 2.54 mm Pin Header PCB Size (mm): 34 x 32 Compatibility: Arduino / Raspberry Pi / Microcontrollers Lifespan: Long-Life, High-Stability Potentiometers Shipping Weight: 0.015 kg Shipping Dimensions (L x W x H): 6 x 5 x 4 cm	PS2 Joystick • Analog Joystick Module • Dual Axis Sensor • 10K Potentiometer Joystick • Arduino Joystick